

	Caliber	Size	Mov't height (mm)	Stem height (mm)	Pinion height (mm)	H (μ)	M (μ)	S (μ)	Subdial position	Balance Weight M (μ N.m) S (μ N.m)		Day/Date /Month	Power Engine	Battery	Battery life (year)
Standard															
Basic	2025	6 3/4 x 8'''	3.15	1.10	1.30	850	450			0.40				SR626SW	3
	2026	6 3/4 x 8'''	3.15	1.10	2.75	2,400	350			0.40				SR626SW	3
	2035	6 3/4 x 8'''	3.15	1.10	1.60	850	400	350		0.40	0.07		●	SR626SW	3
	2036	6 3/4 x 8'''	3.15	1.10	2.10	1,200	500	400		0.40	0.07		●	SR626SW	3
	2039	6 3/4 x 8'''	3.15	1.10	2.30	1,700	300	300		0.40	0.07		●	SR626SW	3
	2033	6 3/4 x 8'''	3.15	1.10	2.56	1,850	460	250		0.40	0.07		●	SR626SW	3
	203A	6 3/4 x 8'''	3.15	1.10	3.35	2,500	400	450		0.40	0.07		●	SR626SW	3
Super 2035	6 3/4 x 8'''	3.15	1.10	1.60	850	400	350			0.40	0.09		●	SR626SW	4
	2037	6 3/4 x 8'''	3.15	1.10	1.60	850	400	350		0.40	0.07		●	SR626SW	3
	2034	6 3/4 x 8'''	3.15	1.10	1.80	850	400	550		0.40	0.07			SR626SW	14 month
	2015	6 3/4 x 8'''	4.15	2.10	1.85	1,100	400	350		0.40	0.07	Date	●	SR626SW	3
	2005	6 3/4 x 8'''	4.15	2.10	1.85	1,100	400	350		0.40	0.07	Day Date	●	SR626SW	3
	2115	10 1/2'''	4.15	2.10	1.85	1,100	400	350		0.40	0.09	Date	●	SR626SW	3
	2117	10 1/2'''	4.15	2.10	2.15	1,400	400	350		0.40	0.09	Date	●	SR626SW	3
	2105	10 1/2'''	4.15	2.10	1.85	1,100	400	350		0.40	0.09	Day Date	●	SR626SW	3
	2315	11 1/2'''	4.15	2.10	1.85	1,100	400	350		0.40	0.09	Date	●	SR626SW	3
	2317	11 1/2'''	4.15	2.10	2.15	1,400	400	350		0.40	0.09	Date	●	SR626SW	3
	2305	11 1/2'''	4.15	2.10	1.85	1,100	400	350		0.40	0.09	Day Date	●	SR626SW	3
	2350	11 1/2'''	4.15	2.10	1.85	1,100	400	350		0.40	0.09	Day Date	●	SR626SW	3
	2415	13 1/2'''	4.35	2.30	1.95	950	500	500		0.40	0.09	Date	●	SR626SW	3
	2417	13 1/2'''	4.35	2.30	2.15	1,200	500	450		0.40	0.09	Date	●	SR626SW	3
	2405	13 1/2'''	4.35	2.30	1.95	950	500	500		0.40	0.09	Day Date	●	SR626SW	3
Small Second	1L40	6 3/4 x 8'''	2.93	1.35	1.60	1,200	400		6	0.40	0.07			SR621SW	3
	1L45	6 3/4 x 8'''	2.93	1.35	1.60	1,200	400		6	0.40	0.07			SR621SW	3
10 Year Battery	1L60	6 3/4 x 8'''	4.30	1.13	1.50	800	400	300		0.40	0.07			CR1616	10
	2S60	10 1/2'''	3.99	1.13	1.50	800	400	300		0.40	0.07	Date		CR2012	10
	2S65	10 1/2'''	4.22	1.36	1.50	850	350	300		0.40	0.07	Day Date		CR2012	10
Slim & Small															
Super Slim	9T22	6 3/4 x 8'''	1.95	0.58	1.15	800	350			0.40				SR616SW	3
	9T15	6 3/4 x 8'''	2.38	1.01	1.08	750	330			0.40		Date		SR616SW	2
	9T33	6 3/4 x 8'''	1.95	0.58	1.43	800	340	290		0.40	0.07			SR616SW	2
	9T13	6 3/4 x 8'''	2.38	1.01	1.38	750	330	300		0.40	0.07	Date		SR616SW	2
	9U15	10 1/2'''	2.38	1.01	1.08	750	330			0.40		Date		SR916SW	4
	9U13	10 1/2'''	2.38	1.01	1.38	750	330	300		0.40	0.07	Date		SR916SW	4
Small	5Y20	5 1/2 x 6 3/4'''	2.54	0.55	1.20	800	400			0.30				SR521SW	4
	5Y26	5 1/2 x 6 3/4'''	2.54	0.55	1.75	1,350	400			0.30				SR521SW	4
	5Y30	5 1/2 x 6 3/4'''	2.54	0.55	1.51	800	400	310		0.30	0.0235			SR521SW	2
	5Y36	5 1/2 x 6 3/4'''	2.54	0.55	2.08	1,350	400	330		0.30	0.0235			SR521SW	2
	Basic Slim	GL22	6 3/4 x 8'''	2.28	0.70	1.15	800	350			0.40				SR621SW
GL24		6 3/4 x 8'''	2.28	0.70	1.60	1,200	400			0.40				SR621SW	5
GL17		6 3/4 x 8'''	2.71	1.13	1.20	800	400			0.40		Date		SR621SW	5
GL32		6 3/4 x 8'''	2.28	0.70	1.45	800	350	300		0.40	0.09		●	SR621SW	3
GL34		6 3/4 x 8'''	2.28	0.70	2.16	1,500	360	300		0.40	0.09		●	SR621SW	3
GL12		6 3/4 x 8'''	2.71	1.13	1.50	800	400	300		0.40	0.09	Date	●	SR621SW	3
GL14		6 3/4 x 8'''	2.71	1.13	2.30	1,450	500	350		0.40	0.09	Date	●	SR621SW	3
GL02		6 3/4 x 8'''	2.94	1.36	1.50	800	400	300		0.40	0.09	Day Date	●	SR621SW	3
GN17		8 3/4'''	2.71	1.13	1.20	800	400			0.40		Date		SR621SW	5
GN12		8 3/4'''	2.71	1.13	1.50	800	400	300		0.40	0.07	Date	●	SR621SW	3
GM17		10 1/2'''	2.71	1.13	1.20	800	400			0.40		Date		SR621SW	5
GM12		10 1/2'''	2.71	1.13	1.50	800	400	300		0.40	0.09	Date	●	SR621SW	3
GM14		10 1/2'''	2.71	1.13	2.30	1,450	500	350		0.40	0.09	Date	●	SR621SW	3
GM02		10 1/2'''	2.94	1.36	1.50	800	400	300		0.40	0.09	Day Date	●	SR621SW	3
Large		GR12	11 1/2'''	2.71	1.13	1.50	800	400	300		0.40	0.09	Date	●	SR621SW
	GR02	11 1/2'''	2.94	1.36	1.50	800	400	300		0.40	0.09	Day Date	●	SR621SW	3
Multi-function															
	6P28	10 1/2'''	3.45	1.60	1.80	1,120	380	300	6	0.40	0.07			SR621SW	3
	6P26	10 1/2'''	3.45	1.60	1.80	1,120	380	300	3	0.40	0.07	Date		SR621SW	3
	6P23	10 1/2'''	3.45	1.60	1.80	1,120	380	300	12, 6	0.40	0.07	Date		SR621SW	3
	6P25	10 1/2'''	3.45	1.60	1.80	1,120	380	300	3, 9	0.40	0.07	Day Date		SR621SW	3
	6P27	10 1/2'''	3.45	1.60	1.80	1,120	380	300	12, 6, 9	0.40	0.07	Day Date		SR621SW	3
	6P29	10 1/2'''	3.45	1.60	1.80	1,120	380	300	3, 6, 9	0.40	0.07	Day Date		SR621SW	3
	6P79	10 1/2'''	3.45	1.60	2.20	1,520	380	300	3, 6, 9	0.40	0.07	Day Date		SR621SW	3
	JP21	12 1/2'''	4.30	2.47	2.10	1,250	450	400	3, 9	0.40	0.09	Day Date	●	SR621SW	3
	JP27	12 1/2'''	4.30	2.47	2.10	1,250	450	400	9	0.40	0.09	Day Date	●	SR621SW	3
Moon-Phase	6P24	10 1/2'''	3.45	1.60	1.80	1,120	380	300		0.40	0.07			SR621SW	3
	6P21	10 1/2'''	3.45	1.60	1.80	1,120	380	300	12, 9	0.40	0.07	Day Date		SR621SW	3
	6P20	10 1/2'''	3.45	1.60	1.80	1,120	380	300	3, 9	0.40	0.07	Day Date		SR621SW	3
	6P00	10 1/2'''	3.45	1.60	1.80	1,120	380	300	12, 3, 9	0.40	0.07	Day Date Month		SR621SW	3
Dual-Time / Long Life Battery															
	JP75	12 1/2'''	5.55	2.47	2.10	1,250	450	400	3, 6, 9	0.40	0.09	Day Date	●	SR621SW	8
Dual-Time	JP11	12 1/2'''	4.30	2.47	2.10	1,250	450	400	12, 6	0.40	0.09	Date	●	SR621SW	3
	JP15	12 1/2'''	4.30	2.47	2.10	1,250	450	400	12, 6, 9	0.40	0.09	Day Date	●	SR621SW	3
	JP25	12 1/2'''	4.30	2.47	2.10	1,250	450	400	3, 6, 9	0.40	0.09	Day Date	●	SR621SW	3
Chronograph															
Regular	0S10	13 1/2'''	4.13	1.28	1.90	1,200	400	300	12, 6, 9	0.40	0.11	Date	●	SR927W	5
	0S00	13 1/2'''	5.10	2.25	1.93	1,200	380	350	12, 6, 9	0.40	0.11	Day Date	●	SR927W	5
	0S30	13 1/2'''	4.13	1.28	1.90	1,200	400	300	12, 6, 9	0.40	0.11		●	SR927W	5
	0S20	13 1/2'''	5.10	2.25	1.93	1,200	380	350	3, 6, 9	0.40	0.11	Date	●	SR927W	5
	0S11	13 1/2'''	4.13	1.28	1.90	1,200	400	300	12, 6	0.40	0.11	Date	●	SR927W	5
	0S21	13 1/2'''	5.10	2.25	1.93	1,200	380	350	3, 9	0.40	0.11	Date	●	SR927W	5
	0S60	13 1/2'''	4.13	1.28	1.90	1,200	400	300	12, 6, 9	0.40	0.11	Date	●	SR927W	2
	Large	6S10	15'''	4.90	1.95	2.55	1,650	450	450	12, 6, 9	1.00	0.40	Date	●	SR927W
6S20		15'''	4.90	1.95	2.55	1,650	450	450	3, 6, 9	1.00	0.40	Date	●	SR927W	4
6S30		15'''	4.90	1.95	2.55	1,650	450	450	2, 6, 10	1.00	0.40	Date	●	SR927W	4
6S11		15'''	4.90	1.95	2.55	1,650	450	450	12, 6	1.00	0.40	Date	●	SR927W	4
6S21		15'''	4.90												

Caliber	Size	Mov't height (mm)	Stem height (mm)	Pinion height (mm)	H (μ)			Subdial position	Balance Weight		Day/Date /Month	Power Engine	Battery	Battery life (year)
					H (μ)	M (μ)	S (μ)		M (μ N.m)	S (μ N.m)				
Small Second Chronograph														
JS15	12 1/2"	4.30	2.47	2.10	1,250	450	400	12, 6, 9	0.40	0.09	Date	●	SR621SW	3
JS16	12 1/2"	4.30	2.47	2.65	1,800	450	400	12, 6, 9	0.40	0.09	Date	●	SR621SW	3
JS10	12 1/2"	4.18	2.35	2.10	1,250	450	400	12, 6, 9	0.40	0.09		●	SR621SW	3
JS25	12 1/2"	4.30	2.47	2.10	1,250	450	400	3, 6, 9	0.40	0.09	Date	●	SR621SW	3
JS26	12 1/2"	4.30	2.47	2.65	1,800	450	400	3, 6, 9	0.40	0.09	Date	●	SR621SW	3
JS20	12 1/2"	4.18	2.35	2.10	1,250	450	400	3, 6, 9	0.40	0.09		●	SR621SW	3
JS05	12 1/2"	4.30	2.47	2.10	1,250	450	400	2, 6, 10	0.40	0.09	Date	●	SR621SW	3
JS06	12 1/2"	4.30	2.47	2.65	1,800	450	400	2, 6, 10	0.40	0.09	Date	●	SR621SW	3
JS00	12 1/2"	4.18	2.35	2.10	1,250	450	400	2, 6, 10	0.40	0.09		●	SR621SW	3
JS36	12 1/2"	4.30	2.47	2.65	1,800	450	400	2, 6, 9	0.40	0.09	Date	●	SR621SW	3
JS50	12 1/2"	4.18	2.35	2.10	1,250	450	400	4, 6, 8	0.40	0.09		●	SR621SW	3
JS55	12 1/2"	4.18	2.35	2.10	1,250	450	400	7, 9, 11	0.40	0.09		●	SR621SW	3

Caliber	Size	Mov't height (mm)	Stem height (mm)	Pinion height (mm)	H (μ)			Subdial	Balance Weight		Day/Date/Montl	Power Engine	Running time
					H (μ)	M (μ)	S (μ)		M (μ N.m)	S (μ N.m)			
Solar Quartz													
2070	13 2/5"	5.98	1.30	1.90	1,000	500	400		0.40	0.09		●	4
2170	16"	5.98	1.30	1.90	1,000	500	400		0.40	0.09		●	4

Caliber	Size	Mov't height (mm)	Stem height (mm)	Pinion height (mm)	H (μ)				Subdial position	Day/Date /Month	Parashock	Frequency (vph)	Duration time (hour)	
					24H (μ)	H (μ)	M (μ)	S (μ)						
Standard Automatic														
Long Power Reserve														
	8315	11 1/2"	5.67	2.52	1.85		1,130	370	350	Date	●	21,600	60	
Standard	8215	11 1/2"	5.67	2.52	1.85		1,130	370	350	Date	●	21,600	42	
	8205	11 1/2"	5.67	2.52	1.85		1,130	370	350	Day Date	●	21,600	42	
Small Hands	8217	11 1/2"	5.67	2.52	2.35		1,250	650	450	Date	●	21,600	42	
Open-Heart	82S0	11 1/2"	5.67	2.52	1.85		1,130	370	350		●	21,600	42	
	82S3	11 1/2"	5.67	2.52	2.35		1,250	650	450	9	●	21,600	42	
	82S5	11 1/2"	5.67	2.52	1.85		1,250	600		5	●	21,600	42	
	82S7	11 1/2"	5.67	2.52	1.85		1,250	600		5, 9	●	21,600	42	
Skeleton	8N24	11 1/2"	5.55	2.00	1.85		1,100	400	350		●	21,600	42	
	8N40	11 1/2"	5.55	2.00	2.37		1,770	600			●	21,600	42	
Premium Automatic														
GMT	9075	11 1/2"	4.92	2.55	2.70	1,200	600	450	450	Date	●	28,800	42	
Slim	9039	11 1/2"	3.90	1.53	1.75		900	400	450		●	28,800	42	
	9019	11 1/2"	3.90	1.53	1.75		900	400	450	Date	●	28,800	42	
	9015	11 1/2"	3.90	1.53	2.10		1,200	450	450	Date	●	28,800	42	
Open-Heart	9029	11 1/2"	3.90	1.53	1.35		900	450			●	28,800	42	
	90S5	11 1/2"	3.90	1.53	2.10		1,200	450	450		●	28,800	42	
Complication	9100	13 1/2"	5.52	2.95	2.55		1,650	450	450	12, 3, 6, 9	Day Date Month	●	28,800	40
	9120	13 1/2"	5.52	2.95	2.55		1,650	450	450	3, 6, 9	Day Date Month	●	28,800	40
	9122	13 1/2"	5.52	2.95	2.55		1,650	450	450	3, 9	Day Date Month	●	28,800	40
	9132	13 1/2"	5.52	2.95	2.55		1,650	450	450	12, 6	Date	●	28,800	40
	9133	13 1/2"	5.52	2.95	2.55		1,650	450	450	9	Date	●	28,800	40
Small Automatic														
	6T27	8 3/4"	5.23	2.05	1.75		990	410	350		●	28,800	40	
	6T15	8 3/4"	5.98	2.80	1.75		1,050	350	350	Date	●	28,800	40	
	6T51	8 3/4"	5.98	2.80	1.75		1,050	350	350	Day Date	●	28,800	40	
	6T28	8 3/4"	5.23	2.05	1.75		990	410	350		●	28,800	40	