



	Caliber	Size	Mov't height	Stem height	Pinion height	Subdial			Balance Weight		Day/Date/Month	Power Engine	Battery	Battery life (year)		
			(mm)	(mm)	(mm)	H (μ)	M (μ)	S (μ)	position	M (μN.m)					S (μN.m)	
<b>Standard</b>																
Basic	2025	6 3/4 x 8'''	3.15	1.10	1.30	850	450		0.40				SR626SW	3		
	2026	6 3/4 x 8'''	3.15	1.10	2.75	2,400	350		0.40				SR626SW	3		
	2035	6 3/4 x 8'''	3.15	1.10	1.60	850	400	350	0.40	0.09		●	SR626SW	3		
	2036	6 3/4 x 8'''	3.15	1.10	2.10	1,200	500	400	0.40	0.09		●	SR626SW	3		
	2039	6 3/4 x 8'''	3.15	1.10	2.30	1,700	300	300	0.40	0.09		●	SR626SW	3		
	203A	6 3/4 x 8'''	3.15	1.10	3.35	2,500	400	450	0.40	0.09		●	SR626SW	3		
	2037	6 3/4 x 8'''	3.15	1.10	1.60	850	400	350	0.40	0.09		●	SR626SW	3		
	2034	6 3/4 x 8'''	3.15	1.10	1.80	850	400	550	0.40					SR626SW	13 month	
	2015	6 3/4 x 8'''	4.15	2.10	1.85	1,100	400	350	0.40	0.09	Date	●	SR626SW	3		
	2005	6 3/4 x 8'''	4.15	2.10	1.85	1,100	400	350	0.40	0.09	Day Date	●	SR626SW	3		
	2115	10 1/2'''	4.15	2.10	1.85	1,100	400	350	0.40	0.09	Date	●	SR626SW	3		
	2117	10 1/2'''	4.15	2.10	2.15	1,400	400	350	0.40	0.09	Date	●	SR626SW	3		
	2105	10 1/2'''	4.15	2.10	1.85	1,100	400	350	0.40	0.09	Day Date	●	SR626SW	3		
	2315	11 1/2'''	4.15	2.10	1.85	1,100	400	350	0.40	0.09	Date	●	SR626SW	3		
	2317	11 1/2'''	4.15	2.10	2.15	1,400	400	350	0.40	0.09	Date	●	SR626SW	3		
	2305	11 1/2'''	4.15	2.10	1.85	1,100	400	350	0.40	0.09	Day Date	●	SR626SW	3		
	2350	11 1/2'''	4.15	2.10	1.85	1,100	400	350	0.40	0.09	Day Date	●	SR626SW	3		
	2415	13 1/2'''	4.35	2.30	1.95	950	500	500	0.40	0.09	Date	●	SR626SW	3		
	2405	13 1/2'''	4.35	2.30	1.95	950	500	500	0.40	0.09	Day Date	●	SR626SW	3		
	Small Second	1L40	6 3/4 x 8'''	2.93	1.35	1.60	1,200	400		0.40	0.07			SR621SW	3	
1L45		6 3/4 x 8'''	2.93	1.35	1.60	1,200	400	6	0.40	0.07			SR621SW	3		
<b>Slim &amp; Small</b>																
Super Slim	9T25	6 3/4 x 8'''	1.95	0.58	1.15	800	350		0.40				SR616SW	3		
	9T17	6 3/4 x 8'''	2.38	1.01	1.08	750	330		0.40		Date		SR616SW	2		
	9T35	6 3/4 x 8'''	1.95	0.58	1.43	800	340	290	0.40	0.07			SR616SW	2		
	9T12	6 3/4 x 8'''	2.38	1.01	1.38	750	330	300	0.40	0.07	Date		SR616SW	2		
	9U17	10 1/2'''	2.38	1.01	1.08	750	330		0.40		Date		SR916SW	2		
	9U12	10 1/2'''	2.38	1.01	1.38	750	330	300	0.40	0.07	Date		SR916SW	2		
Small	5Y20	5 1/2 x 6 3/4'''	2.54	0.55	1.20	800	400		0.30				SR521SW	4		
	5Y26	5 1/2 x 6 3/4'''	2.54	0.55	1.75	1,350	400		0.30				SR521SW	4		
	5Y30	5 1/2 x 6 3/4'''	2.54	0.55	1.51	800	400	310	0.30	0.0235			SR521SW	2		
	5Y36	5 1/2 x 6 3/4'''	2.54	0.55	2.08	1,350	400	330	0.30	0.0235			SR521SW	2		
Basic Slim	GL22	6 3/4 x 8'''	2.28	0.70	1.15	800	350		0.40				SR621SW	5		
	GL24	6 3/4 x 8'''	2.28	0.70	1.60	1,200	400		0.40				SR621SW	5		
	GL17	6 3/4 x 8'''	2.71	1.13	1.20	800	400		0.40		Date		SR621SW	5		
	GL32	6 3/4 x 8'''	2.28	0.70	1.45	800	350	300	0.40	0.09		●	SR621SW	3		
	GL34	6 3/4 x 8'''	2.28	0.70	2.16	1,500	360	300	0.40	0.09		●	SR621SW	3		
	GL12	6 3/4 x 8'''	2.71	1.13	1.50	800	400	300	0.40	0.09	Date	●	SR621SW	3		
	GL02	6 3/4 x 8'''	2.94	1.36	1.50	800	400	300	0.40	0.09	Day Date	●	SR621SW	3		
	GM17	10 1/2'''	2.71	1.13	1.20	800	400		0.40		Date		SR621SW	5		
	GM12	10 1/2'''	2.71	1.13	1.50	800	400	300	0.40	0.09	Date	●	SR621SW	3		
	GM02	10 1/2'''	2.94	1.36	1.50	800	400	300	0.40	0.09	Day Date	●	SR621SW	3		
Large	GR12	11 1/2'''	2.71	1.13	1.50	800	400	300	0.40	0.09	Date	●	SR621SW	3		
	GR02	11 1/2'''	2.94	1.36	1.50	800	400	300	0.40	0.09	Day Date	●	SR621SW	3		
<b>Multi-function</b>																
Moon-Phase	6P28	10 1/2'''	3.45	1.60	1.80	1,120	380	300	6	0.30	0.07		SR621SW	3		
	6P26	10 1/2'''	3.45	1.60	1.80	1,120	380	300	3	0.30	0.07	Date		SR621SW	3	
	6P23	10 1/2'''	3.45	1.60	1.80	1,120	380	300	12, 6	0.30	0.07	Date		SR621SW	3	
	6P25	10 1/2'''	3.45	1.60	1.80	1,120	380	300	3, 9	0.30	0.07	Day Date		SR621SW	3	
	6P27	10 1/2'''	3.45	1.60	1.80	1,120	380	300	12, 6, 9	0.30	0.07	Day Date		SR621SW	3	
	6P29	10 1/2'''	3.45	1.60	1.80	1,120	380	300	3, 6, 9	0.30	0.07	Day Date		SR621SW	3	
	6P79	10 1/2'''	3.45	1.60	2.20	1,520	380	300	3, 6, 9	0.30	0.07	Day Date		SR621SW	3	
	JP21	12 1/2'''	4.30	2.47	2.10	1,250	450	400	3, 9	0.40	0.09	Day Date	●	SR621SW	3	
	JP27	12 1/2'''	4.30	2.47	2.10	1,250	450	400	9	0.40	0.09	Day Date	●	SR621SW	3	
	6P24	10 1/2'''	3.45	1.60	1.80	1,120	380	300		0.30	0.07			SR621SW	3	
	6P20	10 1/2'''	3.45	1.60	1.80	1,120	380	300	3, 9	0.30	0.07	Day Date		SR621SW	3	
	6P00	10 1/2'''	3.45	1.60	1.80	1,120	380	300	12, 3, 9	0.30	0.07	Day Date Month		SR621SW	3	
<b>Dual-Time / Long Life Battery</b>																
Dual-Time	JP11	12 1/2'''	4.30	2.47	2.10	1,250	450	400	12, 6	0.40	0.09	Date	●	SR621SW	3	
	JP15	12 1/2'''	4.30	2.47	2.10	1,250	450	400	12, 6, 9	0.40	0.09	Day Date	●	SR621SW	3	
	JP25	12 1/2'''	4.30	2.47	2.10	1,250	450	400	3, 6, 9	0.40	0.09	Day Date	●	SR621SW	3	
<b>Chronograph</b>																
Regular	0S10	13 1/2'''	4.13	1.28	1.90	1,200	400	300	12, 6, 9	0.40	0.11	Date	●	SR927W	5	
	0S00	13 1/2'''	5.10	2.25	1.93	1,200	380	350	12, 6, 9	0.40	0.11	Day Date	●	SR927W	5	
	0S20	13 1/2'''	5.10	2.25	1.93	1,200	380	350	3, 6, 9	0.40	0.11	Date	●	SR927W	5	
	0S11	13 1/2'''	4.13	1.28	1.90	1,200	400	300	12, 6	0.40	0.11	Date	●	SR927W	5	
	0S21	13 1/2'''	5.10	2.25	1.93	1,200	380	350	3, 9	0.40	0.11	Date	●	SR927W	5	
	0S60	13 1/2'''	4.13	1.28	1.90	1,200	400	300	12, 6, 9	0.40	0.11	Date	●	SR927W	2	
	Large	6S10	15'''	4.90	1.95	2.55	1,650	450	450	12, 6, 9	1.00	0.40	Date	●	SR927W	4
		6S20	15'''	4.90	1.95	2.55	1,650	450	450	3, 6, 9	1.00	0.40	Date	●	SR927W	4
6S30		15'''	4.90	1.95	2.55	1,650	450	450	2, 6, 10	1.00	0.40	Date	●	SR927W	4	
6S11		15'''	4.90	1.95	2.55	1,650	450	450	12, 6	1.00	0.40	Date	●	SR927W	4	
6S21		15'''	4.90	1.95	2.55	1,650	450	450	3, 9	1.00	0.40	Date	●	SR927W	3	



Caliber	Size	Mov't height (mm)	Stem height (mm)	Pinion height (mm)	Subdial			Balance Weight		Day/Date/Month	Power Engine	Battery	Battery life (year)	
					H (μ)	M (μ)	S (μ)	position	M (μN.m)					S (μN.m)
<b>Small Second Chronograph</b>														
JS15	12 1/2'''	4.30	2.47	2.10	1,250	450	400	12, 6, 9	0.40	0.09	Date	●	SR621SW	3
JS16	12 1/2'''	4.30	2.47	2.65	1,800	450	400	12, 6, 9	0.40	0.09	Date	●	SR621SW	3
JS10	12 1/2'''	4.18	2.35	2.10	1,250	450	400	12, 6, 9	0.40	0.09		●	SR621SW	3
JS25	12 1/2'''	4.30	2.47	2.10	1,250	450	400	3, 6, 9	0.40	0.09	Date	●	SR621SW	3
JS26	12 1/2'''	4.30	2.47	2.65	1,800	450	400	3, 6, 9	0.40	0.09	Date	●	SR621SW	3
JS20	12 1/2'''	4.18	2.35	2.10	1,250	450	400	3, 6, 9	0.40	0.09		●	SR621SW	3
JS05	12 1/2'''	4.30	2.47	2.10	1,250	450	400	2, 6, 10	0.40	0.09	Date	●	SR621SW	3
JS00	12 1/2'''	4.18	2.35	2.10	1,250	450	400	2, 6, 10	0.40	0.09		●	SR621SW	3
JS50	12 1/2'''	4.18	2.35	2.10	1,250	450	400	4, 6, 8	0.40	0.09		●	SR621SW	3

Caliber	Size	Mov't height (mm)	Stem height (mm)	Pinion height (mm)	Subdial			Subdial position	Day/Date/Month	Parashock	Frequency (vph)	Approximate duration time (hour)	
					24H (μ)	H (μ)	M (μ)						S (μ)
<b>Standard Automatic</b>													
Long Power Reserve													
	8315	11 1/2'''	5.67	2.52	1.85	1,130	370	350	Date	●	21,600	60	
Standard	8215	11 1/2'''	5.67	2.52	1.85	1,130	370	350	Date	●	21,600	42	
	8205	11 1/2'''	5.67	2.52	1.85	1,130	370	350	Day Date	●	21,600	42	
Small Hands	8217	11 1/2'''	5.67	2.52	2.35	1,250	650	450	Date	●	21,600	42	
Open-Heart	8250	11 1/2'''	5.67	2.52	1.85	1,130	370	350		●	21,600	42	
	8253	11 1/2'''	5.67	2.52	2.35	1,250	650	450	9	●	21,600	42	
	8255	11 1/2'''	5.67	2.52	1.85	1,250	600		5	●	21,600	42	
	8257	11 1/2'''	5.67	2.52	1.85	1,250	600		5, 9	●	21,600	42	
Skeleton	8N24	11 1/2'''	5.55	2.00	1.85	1,100	400	350		●	21,600	42	
	8N40	11 1/2'''	5.55	2.00	2.37	1,770	600			●	21,600	42	
<b>Premium Automatic</b>													
GMT	9075	11 1/2'''	4.92	2.55	2.70	1,200	600	450	450	Date	●	28,800	42
Slim	9039	11 1/2'''	3.90	1.53	1.75	900	400	450		●	28,800	42	
	9015	11 1/2'''	3.90	1.53	2.10	1,200	450	450		Date	●	28,800	42
Open-Heart	9055	11 1/2'''	3.90	1.53	2.10	1,200	450	450		●	28,800	42	
Complication	9100	13 1/2'''	5.52	2.95	2.55	1,650	450	450	12, 3, 6, 9	Day Date Month	●	28,800	40
	9120	13 1/2'''	5.52	2.95	2.55	1,650	450	450	3, 6, 9	Day Date Month	●	28,800	40
	9122	13 1/2'''	5.52	2.95	2.55	1,650	450	450	3, 9	Day Date Month	●	28,800	40
	9132	13 1/2'''	5.52	2.95	2.55	1,650	450	450	12, 6	Date	●	28,800	40
<b>Small Automatic</b>													
	6T27	8 3/4'''	5.23	2.05	1.75	990	410	350		●	28,800	40	
	6T15	8 3/4'''	5.98	2.80	1.75	1,050	350	350		Date	●	28,800	40
	6T51	8 3/4'''	5.98	2.80	1.75	1,050	350	350		Day Date	●	28,800	40
	6T28	8 3/4'''	5.23	2.05	1.75	990	410	350		●	28,800	40	