



	Caliber	Size	Mov't height (mm)	Stem height (mm)	Pinion height (mm)	H (μ)	M (μ)	S (μ)	Subdial position	Balance Weight M (μN.m)	S (μN.m)	Day/Date/Month	Power Engine	Battery	Battery life (year)			
Standard	Basic	2025	6 3/4 x 8'''	3.15	1.10	1.30	850	450		0.40				SR626SW	3			
		2026	6 3/4 x 8'''	3.15	1.10	2.75	2,400	350		0.40				SR626SW	3			
		2035	6 3/4 x 8'''	3.15	1.10	1.60	850	400	350		0.40	0.09		●	SR626SW	3		
		2036	6 3/4 x 8'''	3.15	1.10	2.10	1,200	500	400		0.40	0.09		●	SR626SW	3		
		2039	6 3/4 x 8'''	3.15	1.10	2.30	1,700	300	300		0.40	0.09		●	SR626SW	3		
		203A	6 3/4 x 8'''	3.15	1.10	3.35	2,500	400	450		0.40	0.09		●	SR626SW	3		
		2037	6 3/4 x 8'''	3.15	1.10	1.60	850	400	350		0.40	0.09		●	SR626SW	3		
		2034	6 3/4 x 8'''	3.15	1.10	1.80	850	400	550		0.40				SR626SW	13 month		
		2015	6 3/4 x 8'''	4.15	2.10	1.85	1,100	400	350		0.40	0.09	Date	●	SR626SW	3		
		2005	6 3/4 x 8'''	4.15	2.10	1.85	1,100	400	350		0.40	0.09	Day Date	●	SR626SW	3		
		2115	10 1/2'''	4.15	2.10	1.85	1,100	400	350		0.40	0.09	Date	●	SR626SW	3		
		2117	10 1/2'''	4.15	2.10	2.15	1,400	400	350		0.40	0.09	Date	●	SR626SW	3		
		2105	10 1/2'''	4.15	2.10	1.85	1,100	400	350		0.40	0.09	Day Date	●	SR626SW	3		
		2315	11 1/2'''	4.15	2.10	1.85	1,100	400	350		0.40	0.09	Date	●	SR626SW	3		
		2317	11 1/2'''	4.15	2.10	2.15	1,400	400	350		0.40	0.09	Date	●	SR626SW	3		
		2305	11 1/2'''	4.15	2.10	1.85	1,100	400	350		0.40	0.09	Day Date	●	SR626SW	3		
		2350	11 1/2'''	4.15	2.10	1.85	1,100	400	350		0.40	0.09	Day Date	●	SR626SW	3		
		2415	13 1/2'''	4.35	2.30	1.95	950	500	500		0.40	0.09	Date	●	SR626SW	3		
		2405	13 1/2'''	4.35	2.30	1.95	950	500	500		0.40	0.09	Day Date	●	SR626SW	3		
		Small Second	1L40	6 3/4 x 8'''	2.93	1.35	1.60	1,200	400		6	0.40	0.07			SR621SW	3	
			1L45	6 3/4 x 8'''	2.93	1.35	1.60	1,200	400		6	0.40	0.07			SR621SW	3	
		Slim & Small	Super Slim	9T22	6 3/4 x 8'''	1.95	0.58	1.15	800	350		0.40				SR616SW	3	
				9T15	6 3/4 x 8'''	2.38	1.01	1.08	750	330		0.40			Date	SR616SW	2	
				9T33	6 3/4 x 8'''	1.95	0.58	1.43	800	340	290		0.40	0.07		SR616SW	2	
9T13	6 3/4 x 8'''			2.38	1.01	1.38	750	330	300		0.40	0.07	Date	SR616SW	2			
9U15	10 1/2'''			2.38	1.01	1.08	750	330		0.40			Date	SR916SW	4			
9U13	10 1/2'''			2.38	1.01	1.38	750	330	300		0.40	0.07	Date	SR916SW	4			
Small	5Y20		5 1/2 x 6 3/4'''	2.54	0.55	1.20	800	400		0.30				SR521SW	4			
	5Y26		5 1/2 x 6 3/4'''	2.54	0.55	1.75	1,350	400		0.30				SR521SW	4			
	5Y30		5 1/2 x 6 3/4'''	2.54	0.55	1.51	800	400	310		0.30	0.0235		SR521SW	2			
	5Y36		5 1/2 x 6 3/4'''	2.54	0.55	2.08	1,350	400	330		0.30	0.0235		SR521SW	2			
Basic Slim	GL22		6 3/4 x 8'''	2.28	0.70	1.15	800	350		0.40				SR621SW	5			
	GL24		6 3/4 x 8'''	2.28	0.70	1.60	1,200	400		0.40				SR621SW	5			
	GL17		6 3/4 x 8'''	2.71	1.13	1.20	800	400		0.40			Date	SR621SW	5			
	GL32		6 3/4 x 8'''	2.28	0.70	1.45	800	350	300		0.40	0.09		●	SR621SW	3		
	GL34		6 3/4 x 8'''	2.28	0.70	2.16	1,500	360	300		0.40	0.09		●	SR621SW	3		
	GL12		6 3/4 x 8'''	2.71	1.13	1.50	800	400	300		0.40	0.09	Date	●	SR621SW	3		
	GL02		6 3/4 x 8'''	2.94	1.36	1.50	800	400	300		0.40	0.09	Day Date	●	SR621SW	3		
	GM17		10 1/2'''	2.71	1.13	1.20	800	400		0.40			Date	SR621SW	5			
	GM12		10 1/2'''	2.71	1.13	1.50	800	400	300		0.40	0.09	Date	●	SR621SW	3		
	GM02		10 1/2'''	2.94	1.36	1.50	800	400	300		0.40	0.09	Day Date	●	SR621SW	3		
	Large		GR12	11 1/2'''	2.71	1.13	1.50	800	400	300		0.40	0.09	Date	●	SR621SW	3	
			GR02	11 1/2'''	2.94	1.36	1.50	800	400	300		0.40	0.09	Day Date	●	SR621SW	3	
Multi-function			6P28	10 1/2'''	3.45	1.60	1.80	1,120	380	300	6	0.30	0.07		SR621SW	3		
			6P26	10 1/2'''	3.45	1.60	1.80	1,120	380	300	3	0.30	0.07	Date	SR621SW	3		
		6P23	10 1/2'''	3.45	1.60	1.80	1,120	380	300	12, 6	0.30	0.07	Date	SR621SW	3			
		6P25	10 1/2'''	3.45	1.60	1.80	1,120	380	300	3, 9	0.30	0.07	Day Date	SR621SW	3			
		6P27	10 1/2'''	3.45	1.60	1.80	1,120	380	300	12, 6, 9	0.30	0.07	Day Date	SR621SW	3			
		6P29	10 1/2'''	3.45	1.60	1.80	1,120	380	300	3, 6, 9	0.30	0.07	Day Date	SR621SW	3			
		6P79	10 1/2'''	3.45	1.60	2.20	1,520	380	300	3, 6, 9	0.30	0.07	Day Date	SR621SW	3			
		JP21	12 1/2'''	4.30	2.47	2.10	1,250	450	400	3, 9	0.40	0.09	Day Date	●	SR621SW	3		
		JP27	12 1/2'''	4.30	2.47	2.10	1,250	450	400	9	0.40	0.09	Day Date	●	SR621SW	3		
		Moon-Phase	6P24	10 1/2'''	3.45	1.60	1.80	1,120	380	300		0.30	0.07		SR621SW	3		
			6P20	10 1/2'''	3.45	1.60	1.80	1,120	380	300	3, 9	0.30	0.07	Day Date	SR621SW	3		
			6P00	10 1/2'''	3.45	1.60	1.80	1,120	380	300	12, 3, 9	0.30	0.07	Day Date Month	SR621SW	3		
		Dual-Time / Long Life Battery																
		Dual-Time	JP11	12 1/2'''	4.30	2.47	2.10	1,250	450	400	12, 6	0.40	0.09	Date	●	SR621SW	3	
			JP15	12 1/2'''	4.30	2.47	2.10	1,250	450	400	12, 6, 9	0.40	0.09	Day Date	●	SR621SW	3	
			JP25	12 1/2'''	4.30	2.47	2.10	1,250	450	400	3, 6, 9	0.40	0.09	Day Date	●	SR621SW	3	
		Chronograph	Regular	0S10	13 1/2'''	4.13	1.28	1.90	1,200	400	300	12, 6, 9	0.40	0.11	Date	●	SR927W	5
				0S00	13 1/2'''	5.10	2.25	1.93	1,200	380	350	12, 6, 9	0.40	0.11	Day Date	●	SR927W	5
0S20	13 1/2'''			5.10	2.25	1.93	1,200	380	350	3, 6, 9	0.40	0.11	Date	●	SR927W	5		
0S11	13 1/2'''			4.13	1.28	1.90	1,200	400	300	12, 6	0.40	0.11	Date	●	SR927W	5		
0S21	13 1/2'''			5.10	2.25	1.93	1,200	380	350	3, 9	0.40	0.11	Date	●	SR927W	5		
0S60	13 1/2'''			4.13	1.28	1.90	1,200	400	300	12, 6, 9	0.40	0.11	Date	●	SR927W	2		
Large	6S10		15'''	4.90	1.95	2.55	1,650	450	450	12, 6, 9	1.00	0.40	Date	●	SR927W	4		
	6S20		15'''	4.90	1.95	2.55	1,650	450	450	3, 6, 9	1.00	0.40	Date	●	SR927W	4		
	6S30		15'''	4.90	1.95	2.55	1,650	450	450	2, 6, 10	1.00	0.40	Date	●	SR927W	4		
	6S11		15'''	4.90	1.95	2.55	1,650	450	450	12, 6	1.00	0.40	Date	●	SR927W	4		
	6S21		15'''	4.90	1.95	2.55	1,650	450	450	3, 9	1.00	0.40	Date	●	SR927W	3		



Caliber	Size	Mov't height	Stem height	Pinion height				Subdial position	Balance Weight		Day/Date/Month	Power Engine	Battery	Battery life (year)
		(mm)	(mm)	(mm)	H (μ)	M (μ)	S (μ)		M (μN.m)	S (μN.m)				
Small Second Chronograph														
JS15	12 1/2'''	4.30	2.47	2.10	1,250	450	400	12, 6, 9	0.40	0.09	Date	●	SR621SW	3
JS16	12 1/2'''	4.30	2.47	2.65	1,800	450	400	12, 6, 9	0.40	0.09	Date	●	SR621SW	3
JS10	12 1/2'''	4.18	2.35	2.10	1,250	450	400	12, 6, 9	0.40	0.09		●	SR621SW	3
JS25	12 1/2'''	4.30	2.47	2.10	1,250	450	400	3, 6, 9	0.40	0.09	Date	●	SR621SW	3
JS26	12 1/2'''	4.30	2.47	2.65	1,800	450	400	3, 6, 9	0.40	0.09	Date	●	SR621SW	3
JS20	12 1/2'''	4.18	2.35	2.10	1,250	450	400	3, 6, 9	0.40	0.09		●	SR621SW	3
JS05	12 1/2'''	4.30	2.47	2.10	1,250	450	400	2, 6, 10	0.40	0.09	Date	●	SR621SW	3
JS00	12 1/2'''	4.18	2.35	2.10	1,250	450	400	2, 6, 10	0.40	0.09		●	SR621SW	3
JS50	12 1/2'''	4.18	2.35	2.10	1,250	450	400	4, 6, 8	0.40	0.09		●	SR621SW	3

Caliber	Size	Mov't height	Stem height	Pinion height				Subdial	Balance Weight		Day/Date/Month	Power Engine	Running time
		(mm)	(mm)	(mm)	H (μ)	M (μ)	S (μ)	position	M (μN.m)	S (μN.m)			(month)
Solar Quartz													
2070	13 2/5'''	5.98	1.30	1.90	1,000	500	400		0.40	0.09		●	4
2170	16'''	5.98	1.30	1.90	1,000	500	400		0.40	0.09		●	4

	Caliber	Size	Mov't height (mm)	Stem height (mm)	Pinion height (mm)	24H (μ)	H (μ)	M (μ)	S (μ)	Subdial position	Day/Date/Month	Parashock	Frequency (vph)	Approximate duration time (hour)
Standard Automatic														
Long Power Reserve														
Standard	8315	11 1/2'''	5.67	2.52	1.85		1,130	370	350		Date	●	21,600	60
	8215	11 1/2'''	5.67	2.52	1.85		1,130	370	350		Date	●	21,600	42
	8205	11 1/2'''	5.67	2.52	1.85		1,130	370	350		Day Date	●	21,600	42
Small Hands	8217	11 1/2'''	5.67	2.52	2.35		1,250	650	450		Date	●	21,600	42
Open-Heart	8250	11 1/2'''	5.67	2.52	1.85		1,130	370	350			●	21,600	42
	8253	11 1/2'''	5.67	2.52	2.35		1,250	650	450	9		●	21,600	42
	8255	11 1/2'''	5.67	2.52	1.85		1,250	600		5		●	21,600	42
Skeleton	8257	11 1/2'''	5.67	2.52	1.85		1,250	600		5, 9		●	21,600	42
	8N24	11 1/2'''	5.55	2.00	1.85		1,100	400	350			●	21,600	42
	8N40	11 1/2'''	5.55	2.00	2.37		1,770	600				●	21,600	42
	Premium Automatic													
GMT	9075	11 1/2'''	4.92	2.55	2.70	1,200	600	450	450		Date	●	28,800	42
Slim	9039	11 1/2'''	3.90	1.53	1.75		900	400	450			●	28,800	42
	9015	11 1/2'''	3.90	1.53	2.10		1,200	450	450		Date	●	28,800	42
Open-Heart	9055	11 1/2'''	3.90	1.53	2.10		1,200	450	450			●	28,800	42
Complication	9100	13 1/2'''	5.52	2.95	2.55		1,650	450	450	12, 3, 6, 9	Day Date Month	●	28,800	40
	9120	13 1/2'''	5.52	2.95	2.55		1,650	450	450	3, 6, 9	Day Date Month	●	28,800	40
	9122	13 1/2'''	5.52	2.95	2.55		1,650	450	450	3, 9	Day Date Month	●	28,800	40
	9132	13 1/2'''	5.52	2.95	2.55		1,650	450	450	12, 6	Date	●	28,800	40
Small Automatic														
	6T27	8 3/4'''	5.23	2.05	1.75		990	410	350			●	28,800	40
	6T15	8 3/4'''	5.98	2.80	1.75		1,050	350	350		Date	●	28,800	40
	6T51	8 3/4'''	5.98	2.80	1.75		1,050	350	350		Day Date	●	28,800	40
	6T28	8 3/4'''	5.23	2.05	1.75		990	410	350			●	28,800	40