

	Caliber	Size	Mov't height (mm)	Stem height (mm)	Pinion height (mm)	H (μ)			Subdial position	Balance Weight		Day/Date /Month	Power Engine	Battery	Battery life (year)
						H (μ)	M (μ)	S (μ)		M (μ N.m)	S (μ N.m)				
Standard															
Basic	2025	6 3/4 x 8'''	3.15	1.10	1.30	850	450			0.40				SR626SW	3
	2026	6 3/4 x 8'''	3.15	1.10	2.75	2,400	350			0.40				SR626SW	3
	2035	6 3/4 x 8'''	3.15	1.10	1.60	850	400	350		0.40	0.09		●	SR626SW	3
	2036	6 3/4 x 8'''	3.15	1.10	2.10	1,200	500	400		0.40	0.09		●	SR626SW	3
	2039	6 3/4 x 8'''	3.15	1.10	2.30	1,700	300	300		0.40	0.09		●	SR626SW	3
	2033	6 3/4 x 8'''	3.15	1.10	2.56	1,850	460	250		0.40	0.09		●	SR626SW	3
	203A	6 3/4 x 8'''	3.15	1.10	3.35	2,500	400	450		0.40	0.09		●	SR626SW	3
	Super 2035	6 3/4 x 8'''	3.15	1.10	1.60	850	400	350		0.40	0.09		●	SR626SW	4
	2037	6 3/4 x 8'''	3.15	1.10	1.60	850	400	350		0.40	0.09		●	SR626SW	3
	2034	6 3/4 x 8'''	3.15	1.10	1.80	850	400	550		0.40				SR626SW	14 month
	2015	6 3/4 x 8'''	4.15	2.10	1.85	1,100	400	350		0.40	0.09	Date	●	SR626SW	3
	2005	6 3/4 x 8'''	4.15	2.10	1.85	1,100	400	350		0.40	0.09	Day Date	●	SR626SW	3
	2115	10 1/2'''	4.15	2.10	1.85	1,100	400	350		0.40	0.09	Date	●	SR626SW	3
	2117	10 1/2'''	4.15	2.10	2.15	1,400	400	350		0.40	0.09	Date	●	SR626SW	3
	2105	10 1/2'''	4.15	2.10	1.85	1,100	400	350		0.40	0.09	Day Date	●	SR626SW	3
	2315	11 1/2'''	4.15	2.10	1.85	1,100	400	350		0.40	0.09	Date	●	SR626SW	3
	2317	11 1/2'''	4.15	2.10	2.15	1,400	400	350		0.40	0.09	Date	●	SR626SW	3
	2305	11 1/2'''	4.15	2.10	1.85	1,100	400	350		0.40	0.09	Day Date	●	SR626SW	3
	2350	11 1/2'''	4.15	2.10	1.85	1,100	400	350		0.40	0.09	Day Date	●	SR626SW	3
	2415	13 1/2'''	4.35	2.30	1.95	950	500	500		0.40	0.09	Date	●	SR626SW	3
	2417	13 1/2'''	4.35	2.30	2.15	1,200	500	450		0.40	0.09	Date	●	SR626SW	3
	2405	13 1/2'''	4.35	2.30	1.95	950	500	500		0.40	0.09	Day Date	●	SR626SW	3
Small Second	1L40	6 3/4 x 8'''	2.93	1.35	1.60	1,200	400		6	0.40	0.07			SR621SW	3
	1L45	6 3/4 x 8'''	2.93	1.35	1.60	1,200	400		6	0.40	0.07			SR621SW	3
Slim & Small															
Super Slim	9T22	6 3/4 x 8'''	1.95	0.58	1.15	800	350			0.40				SR616SW	3
	9T15	6 3/4 x 8'''	2.38	1.01	1.08	750	330			0.40		Date		SR616SW	2
	9T33	6 3/4 x 8'''	1.95	0.58	1.43	800	340	290		0.40	0.07			SR616SW	2
	9T13	6 3/4 x 8'''	2.38	1.01	1.38	750	330	300		0.40	0.07	Date		SR616SW	2
	9U15	10 1/2'''	2.38	1.01	1.08	750	330			0.40		Date		SR916SW	4
	9U13	10 1/2'''	2.38	1.01	1.38	750	330	300		0.40	0.07	Date		SR916SW	4
Small	5Y20	5 1/2 x 6 3/4'''	2.54	0.55	1.20	800	400			0.30				SR521SW	4
	5Y26	5 1/2 x 6 3/4'''	2.54	0.55	1.75	1,350	400			0.30				SR521SW	4
	5Y30	5 1/2 x 6 3/4'''	2.54	0.55	1.51	800	400	310		0.30	0.0235			SR521SW	2
	5Y36	5 1/2 x 6 3/4'''	2.54	0.55	2.08	1,350	400	330		0.30	0.0235			SR521SW	2
Basic Slim	GL22	6 3/4 x 8'''	2.28	0.70	1.15	800	350			0.40				SR621SW	5
	GL24	6 3/4 x 8'''	2.28	0.70	1.60	1,200	400			0.40				SR621SW	5
	GL17	6 3/4 x 8'''	2.71	1.13	1.20	800	400			0.40		Date		SR621SW	5
	GL32	6 3/4 x 8'''	2.28	0.70	1.45	800	350	300		0.40	0.09		●	SR621SW	3
	GL34	6 3/4 x 8'''	2.28	0.70	2.16	1,500	360	300		0.40	0.09		●	SR621SW	3
	GL12	6 3/4 x 8'''	2.71	1.13	1.50	800	400	300		0.40	0.09	Date	●	SR621SW	3
	GL14	6 3/4 x 8'''	2.71	1.13	2.30	1,450	500	350		0.40	0.09	Date	●	SR621SW	3
	GL02	6 3/4 x 8'''	2.94	1.36	1.50	800	400	300		0.40	0.09	Day Date	●	SR621SW	3
	GN17	8 3/4'''	2.71	1.13	1.20	800	400			0.40		Date		SR621SW	5
	GN12	8 3/4'''	2.71	1.13	1.50	800	400	300		0.40	0.07	Date	●	SR621SW	3
	GM17	10 1/2'''	2.71	1.13	1.20	800	400			0.40		Date		SR621SW	5
	GM12	10 1/2'''	2.71	1.13	1.50	800	400	300		0.40	0.09	Date	●	SR621SW	3
	GM14	10 1/2'''	2.71	1.13	2.30	1,450	500	350		0.40	0.09	Date	●	SR621SW	3
	GM02	10 1/2'''	2.94	1.36	1.50	800	400	300		0.40	0.09	Day Date	●	SR621SW	3
Large	GR12	11 1/2'''	2.71	1.13	1.50	800	400	300		0.40	0.09	Date	●	SR621SW	3
	GR02	11 1/2'''	2.94	1.36	1.50	800	400	300		0.40	0.09	Day Date	●	SR621SW	3
Multi-function															
	6P28	10 1/2'''	3.45	1.60	1.80	1,120	380	300	6	0.40	0.07			SR621SW	3
	6P26	10 1/2'''	3.45	1.60	1.80	1,120	380	300	3	0.40	0.07	Date		SR621SW	3
	6P23	10 1/2'''	3.45	1.60	1.80	1,120	380	300	12, 6	0.40	0.07	Date		SR621SW	3
	6P25	10 1/2'''	3.45	1.60	1.80	1,120	380	300	3, 9	0.40	0.07	Day Date		SR621SW	3
	6P27	10 1/2'''	3.45	1.60	1.80	1,120	380	300	12, 6, 9	0.40	0.07	Day Date		SR621SW	3
	6P29	10 1/2'''	3.45	1.60	1.80	1,120	380	300	3, 6, 9	0.40	0.07	Day Date		SR621SW	3
	6P79	10 1/2'''	3.45	1.60	2.20	1,520	380	300	3, 6, 9	0.40	0.07	Day Date		SR621SW	3
	JP21	12 1/2'''	4.30	2.47	2.10	1,250	450	400	3, 9	0.40	0.09	Day Date	●	SR621SW	3
	JP27	12 1/2'''	4.30	2.47	2.10	1,250	450	400	9	0.40	0.09	Day Date	●	SR621SW	3
Moon-Phase	6P24	10 1/2'''	3.45	1.60	1.80	1,120	380	300		0.40	0.07			SR621SW	3
	6P20	10 1/2'''	3.45	1.60	1.80	1,120	380	300	3, 9	0.40	0.07	Day Date		SR621SW	3
	6P00	10 1/2'''	3.45	1.60	1.80	1,120	380	300	12, 3, 9	0.40	0.07	Day Date Month		SR621SW	3
Dual-Time / Long Life Battery															
Dual-Time	JP11	12 1/2'''	4.30	2.47	2.10	1,250	450	400	12, 6	0.40	0.09	Date	●	SR621SW	3
	JP15	12 1/2'''	4.30	2.47	2.10	1,250	450	400	12, 6, 9	0.40	0.09	Day Date	●	SR621SW	3
	JP25	12 1/2'''	4.30	2.47	2.10	1,250	450	400	3, 6, 9	0.40	0.09	Day Date	●	SR621SW	3
Chronograph															
Regular	0S10	13 1/2'''	4.13	1.28	1.90	1,200	400	300	12, 6, 9	0.40	0.11	Date	●	SR927W	5
	0S00	13 1/2'''	5.10	2.25	1.93	1,200	380	350	12, 6, 9	0.40	0.11	Day Date	●	SR927W	5
	0S20	13 1/2'''	5.10	2.25	1.93	1,200	380	350	3, 6, 9	0.40	0.11	Date	●	SR927W	5
	0S11	13 1/2'''	4.13	1.28	1.90	1,200	400	300	12, 6	0.40	0.11	Date	●	SR927W	5
	0S21	13 1/2'''	5.10	2.25	1.93	1,200	380	350	3, 9	0.40	0.11	Date	●	SR927W	5
	0S60	13 1/2'''	4.13	1.28	1.90	1,200	400	300	12, 6, 9	0.40	0.11	Date	●	SR927W	2
Large	6S10	15'''	4.90	1.95	2.55	1,650	450	450	12, 6, 9	1.00	0.40	Date	●	SR927W	4
	6S20	15'''	4.90	1.95	2.55	1,650	450	450	3, 6, 9	1.00	0.40	Date	●	SR927W	4
	6S30	15'''	4.90	1.95	2.55	1,650	450	450	2, 6, 10	1.00	0.40	Date	●	SR927W	4
	6S11	15'''	4.90	1.95	2.55	1,650	450	450	12, 6	1.00	0.40	Date	●	SR927W	4
	6S21	15'''	4.90	1.95	2.55	1,650	450	450	3, 9	1.00	0.40	Date	●	SR927W	3

Caliber	Size	Mov't height (mm)	Stem height (mm)	Pinion height (mm)	Subdial			Balance Weight		Day/Date /Month	Power Engine	Battery	Battery life (year)	
					H (μ)	M (μ)	S (μ)	M (μ N.m)	S (μ N.m)					
Small Second Chronograph														
JS15	12 1/2'''	4.30	2.47	2.10	1,250	450	400	12, 6, 9	0.40	0.09	Date	●	SR621SW	3
JS16	12 1/2'''	4.30	2.47	2.65	1,800	450	400	12, 6, 9	0.40	0.09	Date	●	SR621SW	3
JS10	12 1/2'''	4.18	2.35	2.10	1,250	450	400	12, 6, 9	0.40	0.09		●	SR621SW	3
JS25	12 1/2'''	4.30	2.47	2.10	1,250	450	400	3, 6, 9	0.40	0.09	Date	●	SR621SW	3
JS26	12 1/2'''	4.30	2.47	2.65	1,800	450	400	3, 6, 9	0.40	0.09	Date	●	SR621SW	3
JS20	12 1/2'''	4.18	2.35	2.10	1,250	450	400	3, 6, 9	0.40	0.09		●	SR621SW	3
JS05	12 1/2'''	4.30	2.47	2.10	1,250	450	400	2, 6, 10	0.40	0.09	Date	●	SR621SW	3
JS00	12 1/2'''	4.18	2.35	2.10	1,250	450	400	2, 6, 10	0.40	0.09		●	SR621SW	3
JS50	12 1/2'''	4.18	2.35	2.10	1,250	450	400	4, 6, 8	0.40	0.09		●	SR621SW	3

Caliber	Size	Mov't height (mm)	Stem height (mm)	Pinion height (mm)	Subdial			Balance Weight		Day/Date /Month	Power Engine	Running time (month)
					H (μ)	M (μ)	S (μ)	M (μ N.m)	S (μ N.m)			
Solar Quartz												
2070	13 2/5'''	5.98	1.30	1.90	1,000	500	400		0.40	0.09	●	4
2170	16'''	5.98	1.30	1.90	1,000	500	400		0.40	0.09	●	4

Caliber	Size	Mov't height (mm)	Stem height (mm)	Pinion height (mm)	Subdial				Day/Date /Month	Parashock	Frequency (vph)	Duration time (hour)	
					24H (μ)	H (μ)	M (μ)	S (μ)					
Standard Automatic													
Long Power Reserve													
8315	11 1/2'''	5.67	2.52	1.85		1,130	370	350		Date	●	21,600	60
Standard	8215	11 1/2'''	5.67	2.52	1.85	1,130	370	350		Date	●	21,600	42
	8205	11 1/2'''	5.67	2.52	1.85	1,130	370	350		Day Date	●	21,600	42
Small Hands	8217	11 1/2'''	5.67	2.52	2.35	1,250	650	450		Date	●	21,600	42
Open-Heart	82S0	11 1/2'''	5.67	2.52	1.85	1,130	370	350			●	21,600	42
	82S3	11 1/2'''	5.67	2.52	2.35	1,250	650	450	9		●	21,600	42
	82S5	11 1/2'''	5.67	2.52	1.85	1,250	600		5		●	21,600	42
	82S7	11 1/2'''	5.67	2.52	1.85	1,250	600		5, 9		●	21,600	42
Skeleton	8N24	11 1/2'''	5.55	2.00	1.85	1,100	400	350			●	21,600	42
	8N40	11 1/2'''	5.55	2.00	2.37	1,770	600				●	21,600	42
Premium Automatic													
GMT	9075	11 1/2'''	4.92	2.55	2.70	1,200	600	450	450	Date	●	28,800	42
Slim	9039	11 1/2'''	3.90	1.53	1.75	900	400	450			●	28,800	42
	9019	11 1/2'''	3.90	1.53	1.75	900	400	450		Date	●	28,800	42
	9015	11 1/2'''	3.90	1.53	2.10	1,200	450	450		Date	●	28,800	42
Open-Heart	9029	11 1/2'''	3.90	1.53	1.35	900	450				●	28,800	42
	90S5	11 1/2'''	3.90	1.53	2.10	1,200	450	450			●	28,800	42
Complication	9100	13 1/2'''	5.52	2.95	2.55	1,650	450	450	12, 3, 6, 9	Day Date Month	●	28,800	40
	9120	13 1/2'''	5.52	2.95	2.55	1,650	450	450	3, 6, 9	Day Date Month	●	28,800	40
	9122	13 1/2'''	5.52	2.95	2.55	1,650	450	450	3, 9	Day Date Month	●	28,800	40
	9132	13 1/2'''	5.52	2.95	2.55	1,650	450	450	12, 6	Date	●	28,800	40
	9133	13 1/2'''	5.52	2.95	2.55	1,650	450	450	9	Date	●	28,800	40
Small Automatic													
	6T27	8 3/4'''	5.23	2.05	1.75	990	410	350			●	28,800	40
	6T15	8 3/4'''	5.98	2.80	1.75	1,050	350	350		Date	●	28,800	40
	6T51	8 3/4'''	5.98	2.80	1.75	1,050	350	350		Day Date	●	28,800	40
	6T28	8 3/4'''	5.23	2.05	1.75	990	410	350			●	28,800	40